



## PLC-XTC50L

- World's first projector with automatic lamp selection system
- Brightness: 5,000 ANSI lumens, contrast ratio: 1,100 : 1
- XGA Resolution (1.024 x 768 pixels) in 4 : 3 format
- Automatic filter exchange for maintenance-free operation up to 10,000 hours
- Flexible installation with lens shift, keystone correction and 360° projection
- Mechanical shutter for a complete dimout of the light output
- 3 years warranty

## PLC-XTC50L

TECHNICAL DATA	PLC-XTC50L
EAN Code	4994334263933
Category	Professional
Panel	3 x 1.0 " TFT p-Si (4:3)
Panel type	Long-life LCD panel
Lamp	2 x 330 W NSH (LMP-125)
Brightness	5000 ANSI lumens
Brightness (eco mode)	4000 ANSI lumens
Lamp life	3000 h (eco mode) / 2500 h (normal mode)
Fan noise	32 dB (eco mode) / 36 dB (normal mode)
Standard lens	Delivery without lens *
Contrast ratio	1100 : 1
Resolution in pixels	1,024 x 768 (XGA)
Image size min. - max. (diagonal):	30 - 300 inch
Uniformity	90 %
Bandwidth/Frequency	140 MHz, Horizontal : 15 - 100 kHz, Vertical : 50 - 100 Hz
Colour systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: DVI-D (digital/HDCP) Input 2: D-Sub15 (RGB) Input 3: 5 x BNC (RGBHV/Video/Y-Pb/Cb-Pr/Cr) Input 4: Mini DIN 4 (S-Video) Input 5: RCA (Composite) Audio: 3.5 mm Stereo Jack Audio: 2 x RCA (R/L mono) Audio output : 3.5 mm Stereo Jack Monitor output: D-Sub15 Control Input Jack 1: D-Sub9 (RS232) Control Input Jack 2: USB type B Control Input Jack 3: 3.5 mm Stereo Jack (cable remote control)
Audio function	2 x 3 W stereo
Keystone correction	vertical +/- 40°, horizontal +/- 20°
Lens shift	10 : 0 - 1 : 1 vertical (applies to LNS-S11/W10/T10/T11), 1 : 1 vertical (applies to LNS-W11), 1.857 : 1 - 1 : 1.857 horizontal (applies to LNS-S11/W10/T10/T11), 1 : 1 horizontal (applies to LNS-W11)
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,035i, 1,080i
Computer compatibility	U-XGA, S-XGA, S-XGA+, W-XGA, XGA, S-VGA, VGA, Mac
Zoom/Focus	Depending on lens
Power consumption	440 W (eco mode) / 495 W (normal mode), 3.5 W (stand-by mode)
Voltage	100 - 240 V
Warranty	3 years, 24-hr replacement service (D/CH//F - except overseas), 90 days lamp warranty (max. 300 hours)
Dimensions (W x H x D)	451.0 x 175.0 x 550.1 mm
Weight (Net)	14.7 kg
Standard accessories	IR remote control with laser pointer and mouse function, Batteries, User manual, Power cable, USB cable, D-Sub15 cable, PIN code label
Optional accessories	PJ Net Organizer Plus II with video camera (POA-PN03C), Ceiling mount 15 cm (POA-CM01), Ceiling mount 40-70 cm (POA-CM02), Ceiling mount 70-110 cm (POA-CM03), Exchange filter (POA-FIL-100)
Lenses	LNS-S11, LNS-T10, LNS-T11, LNS-W10, LNS-W11

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 04/2009

