

# PLC-XU305

## XGA Ultraportable Multimedia Projector



### A SIMPLE WIRELESS SETTING FOR USE WITH A USB MEMORY

The PLC-XU305 has an innovative wireless feature called "Simple Wireless Set Up". This model can set up a wireless connection easily without installing a software from a CD-ROM. Just pass off the USB memory. By connecting the PC and USB memory, the program in the PLC-XU305 starts running automatically, and the image will be projected directly on the screen.

### NETWORKING CAPABILITY

Bright 3000lm, the PLC-XU305 is equipped with SANYO's exclusive PJ-Net Master Network Interface software for wired and wireless networking, a common feature among SANYO's extensive line of commercial projectors. Networking allows the monitoring of projector functions and operation from a long distance via a web browser for up to 15,000 Sanyo projectors. Emails can be sent automatically to report operating status.

### COMPLETE EASY AUTO SET UP FUNCTION, SMART AUTO INPUT SEARCH AND AUTO VERTICAL KEYSTONE CORRECTION

PLC-XU305 provides "Auto Set Up Function" that corrects keystone shaped distortion by searching for an input signal and detecting projector incline, therefore reducing set up time. PLC-XU305 automatically compensates for keystone picture distortion. Auto Keystone Correction, Auto Input Search and Auto PC Adjustment make it a really smart projector.

### SHORT THROW LENS WITH 1.6 ZOOM AND 7W SPEAKER

PLC-XU305 is equipped with a zoom lens that allows screen size adjustment. The optical zoom works to maintain the image quality. The short-focus type lens allows large screen image projections with a short throw distance. The PLC-XU305 enables 100-inch screen projection at the shortest distance, 80 inches. Along with its mobility, the PLC-XU305 features a high-output 7 Watt speaker. Sufficient audio is delivered through its built-in speaker, so the projector can be used in conference rooms, classrooms, and other similar spaces.

### BLACK BOARD / COLOR BOARD MODE

What could be more right for education? A black board mode. The PLC-XU305 is compatible with four colored (red, blue, green and yellow) projection surfaces via the 'Color Board Mode'. It adjusts the color to make images look as true as on an ordinary white screen.

### LAMP REPLACEMENT ON TOP CABINET

There is access to the lamp from the top of the projector which means you can replace the lamp on a ceiling-mounted unit without taking down the projector.



PRESENTATION TECHNOLOGIES

21605 Plummer Street  
 Chatsworth, CA 91311  
 Ph: 888-337-1215 (toll-free)  
 Fax 818.717.2719  
[www.sanyoprojectors.com](http://www.sanyoprojectors.com)

## Specifications

Resolution	XGA (1,024 x 768)	
Brightness (typical)	3000	
Uniformity	85%	
Panel System	0.63" TFT Poly3	
Number of Pixels	2,359,296 (786,432 x3)	
Contrast Ratio (Full on / off)	500:1	
Image Size	30"-300"	
Aspect Ratio	4:3	
Projection Lamp (s)	225W UHP	
Scanning Frequency	H:15-100kHz V:50-100Hz	
Dot Clock	140MHz	
Fan Noise	29dBA(Eco) 34dBA(Normal)	
Voltage	100-240V	
BTU Rating	1,126 (Normal) 860W(Eco)	
Power Consumption	330W (Normal) 252W(Eco)	
Input signal compatibility	UXGA / WXGA / SXGA+ / SXGA / XGA / SVGA / VGA / MAC, 480i / 480p / 575i / 575p / 720p / 1080i	
Color System	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N	
Projection Lens (inch)	F1.65 - 2.33 f=0.61" - 0.97"	
Throw Ratio	1.18-1.91:1	
Throw Distance (feet)	2.26' - 23.72'	
Zoom / Focus	Manual	
Zoom Ratio	1:1.6	
Up / Down Ratio	9:1	
Digital Keystone Correction	V +/- 30° (Auto Keystone)	
Projection System	Diachronic mirror & X prism system w/PBS	
Digital Zoom	16x - 1/4x	
Speaker Output	7W	
Weight (lbs.)	6.4	
Dimensions (inch) W,H,D	17.3"x9.4"x16.9"	
Replacement Lamp	610 343 2069	
Replacement Remote	645 099 3220	
Input	PC1	Dsub-15 x 1 (RGB, Component, Scart RGB)
		Mini jack x 1 (Audio input, stereo)
	PC2	DVI-I x 1 (Digital & Analog)
		Mini jack x 1 (Audio input, stereo)
	VIDEO	Mini DIN 4-pin x 1 (S-Video)
		RCA x 1 (Composite Video)
		RCA x 2 (Audio input, R/ L-mono)
Out Put		Dsub-15 x 1 (Monitor out)
		Mini jack x 1 (Audio out, stereo variable)
Control 1		Dsub-9 x 1 (Control port)
		USB-B x 1 (Mouse control)
Others		RJ-45 x 1 (Wired LAN)
		USB-A x 1 (Memory viewer)
Included Accessories		Quick reference guide, CD-ROM read me note, UL cable card, PIN code label, Computer cable, Power cord, Remote control, AAA Battery x 2, User's manual (CD ROM), Network Viewer & Capture software (CD ROM), Easy wireless setup software (USB Memory), Soft carrying case, Strap for Lens cap
Optional Accessories		POA-CACOMPVGA-Component Video Cable
User Maintenance		Clean air filters, replace lamp assembly
Warranty		Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



Rear Back Panel

# PLC-XU355

## XGA Ultraportable Multimedia Projector



### A SIMPLE WIRELESS SETTING FOR USE WITH A USB MEMORY

The PLC-XU355 has an innovative wireless feature called "Simple Wireless Set Up". This model can set up a wireless connection easily without installing a software from a CD-ROM. Just pass off the USB memory. By connecting the PC and USB memory, the program in the PLC-XU355 starts running automatically, and the image will be projected directly on the screen.

### NETWORKING CAPABILITY

Bright 3500lm, the PLC-XU355 is equipped with SANYO's exclusive PJ-Net Master Network Interface software for wired and wireless networking, a common feature among SANYO's extensive line of commercial projectors. Networking allows the monitoring of projector functions and operation from a long distance via a web browser for up 15,000 Sanyo projectors. Emails can be sent automatically to report operating status.

### COMPLETE EASY AUTO SET UP FUNCTION, SMART AUTO INPUT SEARCH AND AUTO VERTICAL KEYSTONE CORRECTION

PLC-XU355 provides "Auto Set Up Function" that corrects keystone shaped distortion by searching for an input signal and detecting projector incline, therefore reducing set up time. PLC-XU355 automatically compensates for keystone picture distortion. Auto Keystone Correction, Auto Input Search and Auto PC Adjustment make it a really smart projector.

### SHORT THROW LENS WITH 1.6 ZOOM AND 7W SPEAKER

PLC-XU355 is equipped with a zoom lens that allows screen size adjustment. The optical zoom works to maintain the image quality. The short-focus type lens allows large screen image projections with a short throw distance. The PLC-XU355 enables 100-inch screen projection at the shortest distance, 80 inches. Along with its mobility, the PLC-XU355 features a high-output 7 Watt speaker. Sufficient audio is delivered through its built-in speaker, so the projector can be used in conference rooms, classrooms, and other similar spaces.

### BLACK BOARD / COLOR BOARD MODE

What could be more right for education? A black board mode. The PLC-XU355 is compatible with four colored (red, blue, green and yellow) projection surfaces via the 'Color Board Mode'. It adjusts the color to make images look as true as on an ordinary white screen.

### LAMP REPLACEMENT ON TOP CABINET

There is access to the lamp from the top of the projector which means you can replace the lamp on a ceiling-mounted unit without taking down the projector.



PRESENTATION TECHNOLOGIES

21605 Plummer Street  
 Chatsworth, CA 91311  
 Ph: 888-337-1215 (toll-free)  
 Fax 818.717.2719  
 www.sanyoprojectors.com

## Specifications

Resolution	XGA (1,024 x 768)	
Brightness (typical)	3500 Alm	
Uniformity	85%	
Panel System	0.63" TFT Polyx3	
Number of Pixels	2,359,296 (786,432 x3)	
Contrast Ratio (Full on / off)	500:1	
Image Size	30"-300"	
Aspect Ratio	4:3	
Projection Lamp (s)	225W UHP	
Scanning Frequency	H:15-100kHz, V:50-100Hz	
Dot Clock	140MHz	
Fan Noise	29dBA(Eco) 34dBA(Normal)	
Voltage	100-240V	
BTU Rating	1,126 (Normal) 860W(Eco)	
Power Consumption	330W (Normal) 252W(Eco)	
Input signal compatibility	UXGA / WXGA / SXGA+ / SXGA / XGA / SVGA / VGA / MAC, 480i / 480p / 575i / 575p / 720p / 1080i	
Color System	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N	
Projection Lens (inch)	F1.65 - 2.33 f=0.61" - 0.97"	
Throw Ratio	1.18-1.91:1	
Throw Distance (feet)	2.26' - 23.72'	
Zoom / Focus	Manual	
Zoom Ratio	1:1.6	
Up / Down Ratio	9:1	
Digital Keystone Correction	V +/- 30° (Auto Keystone)	
Projection System	Diachronic mirror & X prism system w/PBS	
Digital Zoom	16x - 1/4x	
Speaker Output	7W	
Weight (lbs.)	6.4 lbs	
Dimensions (inch) W,H,D	17.3"x9.4"x16.9"	
Replacement Lamp	610 343 2069	
Replacement Remote	645 099 3220	
INPUT	PC1	Dsub-15 x 1 (RGB, Component, RGB)
		Mini jack x 1 (Audio input, stereo)
	PC2	DVI-I x 1 (Digital & Analog)
		Mini jack x 1 (Audio input, stereo)
	VIDEO	Mini DIN 4-pin x 1 (S-Video)
		RCA x 1 (Composite Video) RCA x 2 (Audio input, R/ L-mono)
OUT PUT	Dsub-15 x 1 (Monitor out)	
	Mini jack x 1 (Audio out, Stereo variable)	
CONTROL 1	Dsub-9 x 1 (Control port)	
	USB-B x 1 (Mouse control)	
OTHERS	RJ-45 x 1 (Wired LAN)	
	USB-A x 1 (Memory viewer)	
Included Accessories	User's manual (CD ROM),UL cable card, Computer cable (Dsub15—Dsub15),Power cord, Remote control, AAA Battery x 2, Network Viewer & Capture software (CD ROM),Easy wireless setup software (USB Memory), Soft carrying case, Strap for Lens cap	
Optional Accessories	POA-CACOMPVGA-Component Video Cable	
User Maintenance	Clean air filters, replace lamp assembly	
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty	

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



Rear Back Panel